



LP 38x50.18/N5 TW 8Ω

Dome Tweeter

0,7" | 50 W

Code Z008701

- 0,7" voice coil Epotex former
- TSD Treated Silk dome
- FF Ferrofluid in Air Gap
- Neodymium Magnet Circuit
- 91.1 dB sensitivity



Frequency Response on IEC Baffle (DIN 45575) @ 1W,1m – Free Air Impedance

General Specifications

Nominal Dimensions	38x50 mm
Nominal Impedance	8 Ω
Rated Power AES ⁽¹⁾	12 W
Continuous Program Power ⁽²⁾	24 W
Rated Noise Power (IEC 60268-5) ⁽³⁾	50 W
Sensitivity @ 1W/1m ⁽⁴⁾	91.1 dB
Voice Coil Diameter	18 mm (0,7")
Voice Coil Winding Depth	1.7 mm
Magnetic Gap Depth	2.0 mm
Flux Density	1.10 T
DC Resistance	5.8 Ω
Resonance Frequency	2.2 kHz
Magnet Weight	5 g
Net Weight	0.03 kg
Recommended Crossover Frequency	4.5 kHz

Constructive Characteristics

Magnet	Neodymium
Voice Coil Winding Material	Copper
Voice Coil Former Material	Epotex
Diaphragm	Treated Silk
Ferrofluid in Air Gap	Yes
Flange	Nylon Fiberglass Doped
Spare Part Code	-

Mounting Information

Overall Diameter	38x50 mm
Baffle Cutout Diameter	34 mm
Mounting Holes	4 holes ø3,8 on ø46 mm
Total Depth	16.6 mm

(1) Rated Power measured with 2-hour test with pink noise signal, 6dB crest factor. (2) Power on Continuous Program is defined as 3dB greater than the Rated Power. (3) Rated Noise Power measured with 100 hours test pink noise, 6 dB crest factor IEC60268-5 filtering. (4) Measured at 1W, 1m in axis within the frequency range